


Date:	22.04.2021
Revision:	Rev1

**TECHNICAL SPECIFICATION E250D2MST-N
MOBILE TRAILER TYPE 200 kW DIESEL ELECTRIC GENERATING SET**



Generating set model	E250D2MST-N
Manufacturer	SIA "RĪGAS DĪZELIS DG"
Execution	In canopy, on trailer
Prime Power (PRP)	200 kW (250 kVA)
Standby Power (ESP)	210 kW (275 kVA)
Frequency	50 Hz \pm 3%
Voltage	3 phase, 400/230 V \pm 1.5%
Standards compliance	European Union directives: 2006/42 / EC, 2014/35 / EC, 2014/30 / EC, 2000/14 / EC, 97/68 / EC ISO 8528-1, ISO 8528-5, ISO 8528-13.4.3
Governing standards	G3
Emission class	Stage IIIA
Operating environment	-30°C to +40°C
Dimensions (including trailer)	5985 x 2005 x 2870(H) mm
Weight (filled with all liquids & including trailer)	~4500 kg
Engine	TCD2013L06 4V DEUTZ (Germany)
Number of cylinders	L-6
Speed	1500 RPM
Cooling system	Radiator, engine heater
Starting system	Electric starter with starting batteries, charging alternator on engine and static charging device
Exhaust system	Upward exhaust system with flexible compensator and silencer (integrated inside the canopy)
Fuel	According to EN590
Consumption at 100% load	55,9 l
Alternator	Mecc Alte (Italy), or EU analog
Execution	Single bearing, self-excited, brushless, with AVR

All data presented in this document is informative and non-binding. All data in this document is for information only and may be changed without notice.

This document is the intellectual and industrial property of SIA RĪGAS DĪZELIS DG. This document may not be used in commercial or legal affairs without a prior legal and written authorization of SIA RĪGAS DĪZELIS DG.

Protection class	IP23
Insulation class	H
Control panel	Based on microprocessor controller
Control and protection	According to customer's requirements
Protection	IP65
AMF & ATS function	+
Emergency stop button	+
Canopy	Weather proof, "SILENT" type, with lockable service doors
Noise level	69 dBA at 7 m
Color	RAL 6031, 6003 or other at request of the customer
Built in frame fuel tank	Volume enough for 12 h operation at 100% load
Sockets (under request)	Min. 2 pcs. 230 V & 1 pc. 400 V Socket protection class – IP67
Pockets in frame for lifting by forklift	+
Lifting loops on canopy roof and frame	+
Trailer	Two-axle, heavy duty high speed trailer, suitable for speed at least 60 km/h
Coupling mechanism	Height-adjustable
Towing eye	Ø76 mm (acc. STANAG 4101)
Brakes	Pneumatic (in accordance to actual requirements for trailers in end customer country)
ABC	+
Wheels	With winter tires
Connection to the vehicle	12-pins plug (in accordance with STANAG 4135)
Clearance	At least 30 cm
Color	RAL 6031, 6003 or other at request of the customer
Spare wheel	+
6 kg powder fire extinguisher	+
Lifting loops for lifting by crane (together with generating set)	+
Road safety Insurance included	+ (1 year)
Registration in Road Police office included	Registration of Trailer with generating set as one-piece vehicle (not only separate trailer)
Included options	
Power cable	+ (25 m)
Equipment for connecting external batteries for generating set starting	VDA 72593 or equivalent socket; 2-pole, 24 V, 4 m cable, 2x35 mm ² , with VDA 72593 or equivalent plugs
Grounding equipment set with 15 m cable	+
Set of tools for maintenance	+
Set of filters for maintenance during warranty period (but not more than 1000 operating hours)	+
Documentation	
Operational manual for complete generating set	+ (English language, other languages on request)
Spare parts catalogs	+ (in English language)
Package of design documentation (drawings, diagrams, etc.)	+ (in English language)
CE certificate of conformity	+
Factory test report	+
Other	
Delivery	On request

All data presented in this document is informative and non-binding. All data in this document is for information only and may be changed without notice.

This document is the intellectual and industrial property of SIA RĪGAS DĪZELIS DG. This document may not be used in commercial or legal affairs without a prior legal and written authorization of SIA RĪGAS DĪZELIS DG.

Acceptance	Fuel for 30 min. test is included
Training	Customer's personal training is included (during generating set acceptance)
Warranty	24 months from delivery (but not more than 1000 operating hours)
Maintenance	On request

Excluded options	
1	Special fuel type engine liquid preheater
2	Parallel operation with other generating sets and / or mains
3	Additional 20 l fuel can(s) for installation on trailer

Address: 36 Ganību dambis, Rīga, Latvia,
LV-1005

Telephone: +371 67391781, +371 67381626

Fax: +371 67381925

All data presented in this document is informative and non-binding. All data in this document is for information only and may be changed without notice.

This document is the intellectual and industrial property of SIA RĪGAS DĪZELIS DG. This document may not be used in commercial or legal affairs without a prior legal and written authorization of SIA RĪGAS DĪZELIS DG.

E-mail: sales@rigasdizelis.lv
Website: www.rigasdizelis.lv



ANNO 1949

All data presented in this document is informative and non-binding. All data in this document is for information only and may be changed without notice.

This document is the intellectual and industrial property of SIA RĪGAS DĪZELIS DG. This document may not be used in commercial or legal affairs without a prior legal and written authorization of SIA RĪGAS DĪZELIS DG.